

Listing of Claims

Claim 1 (currently amended):

A crane support comprising:

- (a) a pedestal having ~~an~~ a crane supporting upper end, and having a front end, a rear end, and a lateral and longitudinal ~~axes~~ axis extending from the front end to the rear end;
- (b) crane mounting means fixedly attached to or formed wholly with the crane supporting upper end of the pedestal; and,
- (c) ~~first and second~~ means for alternately pivoting and counter-pivoting the pedestal, ~~said the~~ means for alternately pivoting and counter-pivoting the pedestal being connected operatively to the pedestal, and ~~said the~~ means for alternately pivoting and counter-pivoting the pedestal ~~respectively~~ controlling ~~rotating~~ pivoting movements of the pedestal about the ~~lateral and longitudinal axes~~ axis.

Claim 2 (canceled)

Claim 3 (currently amended):

The crane support of Claim 2 1 wherein the ~~second~~ means for alternately pivoting and counter-pivoting the pedestal comprises an axle, ~~said second means being further operatively connected to the mounting frame.~~

Claim 4 (currently amended):

The crane support of Claim 3 wherein the ~~second~~ means for alternately pivoting and counter-pivoting the pedestal further comprises laterally extending outriggers, each laterally extending outrigger having a proximal end and a distal end.

Claim 5 (canceled).

Claim 6 (currently amended):

The crane support of Claim 5 4 wherein the laterally extending outriggers comprise a plurality of segments and first telescoping means connected operatively to the segments for alternately laterally extending and retracting the distal ends of the laterally extending outriggers.

Claim 7 (currently amended):

The crane support of Claim 6 wherein the ~~second~~ means for alternately pivoting and counter-pivoting the pedestal further comprises ~~segmented feet~~ a first plurality of quill and slide shaft combinations attached to the distal ends of the laterally extending outriggers, and second telescoping means being operatively connected to the ~~segmented feet~~ first plurality of quill and slide shaft combinations, the second telescoping means being adapted for alternately downwardly extending and upwardly retracting the ~~segmented feet~~ first plurality of quill and slide shaft combinations.

Claim 8 (previously presented):

The crane support of Claim 7 further comprising releasable locking means connected operatively to the pedestal, the releasable locking means being adapted for alternately resisting and permitting pivoting motions of the pedestal about the longitudinal axis.

Claim 9 (previously presented):

The crane support of Claim 8 wherein the first and second telescoping means comprise a plurality of hydraulic cylinders.

Claim 10 (previously presented):

The crane support of Claim 9 wherein the releasable locking means comprises a hydraulic cylinder.

Claim 11 (previously presented):

The crane support of Claim 10 wherein the laterally extending outriggers' segments comprise a ~~first~~ second plurality of quill and slide shaft combinations.

Claim 12 (canceled).

Claim 13 (currently amended):

The crane support of Claim ~~12~~ 11 wherein the pedestal has a lower end, and further comprising a base fixedly attached to or formed wholly with the lower end.

Claim 14 (previously presented):

The crane support of Claim 13 wherein the first and second pluralities of quill and slide shaft combinations comprise lengths of steel square tubing.

Claim 15 (previously presented):

The crane support of Claim 14 wherein the pedestal comprises a length of steel square tubing.

Claim 16 (previously presented):

The crane support of Claim 4 further comprising a forwardly and downwardly extending outrigger fixedly attached to the pedestal.

Claim 17 (previously presented):

The crane support of Claim 16 wherein the forwardly and downwardly extending outrigger comprises a quill and slide shaft combination.

Claim 18 (previously presented):

The crane support of Claim 17 wherein the forwardly and downwardly extending outrigger further comprises a two way hydraulic cylinder mounted for alternate extension and retraction of the slide shaft.